


Watertight Boxes with fast screw **NEW!**



DIMENSION MM: 115X115X65



APPLICATION STANDARDS: IEC 60670 – 1/2002

GENERAL DESCRIPTION:

- Non-corrosive. Resistant to impact and pressure.
- Made of durable polymer material.
- Flame retardant. Self extinguishing.
- UV protection.
- Outdoor and indoor residential and industrial installations.
- Motion installations – Equipment power supply – Lighting.

Bigger dimension, more space

New Watertight Boxes with fast screw


WATERTIGHT JUNCTION BOXES WITH CABLE GLANDS

- Ø 65x35 IP54
- Ø 80x40 IP54
- 65x65x40 IP54
- 80x80x40 IP54
- 115x115x65 IP55
- 120x80x50 IP55
- 150x110x70 IP55
- 190x140x70 IP55




WATERTIGHT JUNCTION BOXES WITH KNOCK OUTS

- 80x80x40 IP54
- 115x115x65 IP55
- 120x80x50 IP55
- 150x110x70 IP55
- 190x140x70 IP55



WATERTIGHT JUNCTION BOXES WITH BLANK SIDES

- 190x145x70 IP65
- 245x190x90 IP65
- 300x215x125 IP65
- 380x300x125 IP65



PROPERTIES

Protection rating against solid bodies and water:	IP 54; IP 55; IP 65
Glow wire test:	850°C
Minimum temperature limit:	- 15°C
Maximum temperature limit:	+60°C

APPLICATION STANDARDS: IEC 60670 – 1/2002